TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1555-56)

Set ¼ sec. post, from which
A Fir 40" dia., bears N.29½°W., 61 lks. dist.
A Laurel 6" dia., bears S.33°E., 85 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13682)

The ¼ sec. cor. of secs. 25 and 26, determined at record bearing and distance from the original bearing trees:
A Madrone 18" dia., bears S.33°E., 85 lks. dist. with fragmentary scribe marks visible onopened blaze.
A Fir 60" dia., bears N.29½°W., 61 lks. dist., with no marks remaining on opened blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 26 S 25
T 22 S R 8 W
1964
from which new bearing trees:
A Fir 18" dia., bears N.80°E., 44 lks. dist. mkd. ¼ S25 BT.
A Chinquapin 11" dia., bears N.80°W., 70 lks. dist. mkd. ¼ S26 BT.

Survey by Donald L. Branch, L.S. #1137 - For: International Paper Co. - Jan/Feb. 1986 - M 100-31

Found - A 1964 BLM brass cap on a 2" iron pipe.
24" Fir stump bears N.79°54'E., 27.83 ft. dist.
18" Chinquapin bears N.78°33'W., 46.35 ft. dist.
New BT - 13" Chinquapin bears S.33°44'E., 58.16 ft. dist. scribed ¼ S25 BT.

Fd. OK, Feb. 1992, K. Hoffine, M 114-47