

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1596)

 Set Fir post for cor. to secs. 1, 2, 11 and 12, from which
 A Fir 24" dia., bears N.30°E., 25 lks. dist.
 A Fir 48" dia., bears S.26°E., 89 lks. dist.
 A Fir 48" dia., bears S.5°W., 71 lks. dist.
 A Fir 30" dia., bears N.55°W., 21 lks. dist.

Survey by Ben B. Irving - For: Oliver Haines - Nov. 24, 1929 - Vol. 4 Page 4

 Renew this corner by setting a sandstone 7" x 12" x 28" long, securely in the ground and supported by a mound of rocks in the location as determined from all original BTs:
 Reblazed and scribed all BTs:
 24" Fir N.30°E., 25 lks.
 48" Fir S.26°E., 89 lks.
 48" Fir S.5°W., 71 lks.
 30" Fir N.55°W., 21 lks.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - C.S. File 52/14-134 - Oct. 4, 1962

 Corner searched for, not found. Fd. wooden stake and cruiser's marks only.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14109-10)

 The cor. of secs., determined at record bearing and distance from the original bearing trees
 A stump hole and Fir roots, bears N.30°E., 25 lks. dist.
 A broken Fir snag 54" dia., bears S.26°E., 89 lks. dist. with fragmentary scribe marks visible on bottom of bark blaze.
 A stump hole bears S.5°W., 71 lks. dist.
 A down and rotted Fir 30" dia., bears N.55°W., 21 lks. dist. no marks visible.

At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

T	22	S	R	8	W
	S	2	S	1	
	S	11	S	12	
				1967	

from which

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 6" dia., bears N.19°E., 62 lks. dist. mkd. T22S R8W S1 BT.
A Fir 4" dia., bears S.16°E., 139 lks. dist. mkd. T22S R8W S12 BT.
A Hemlock 6" dia., bears S.21°W., 16 lks. dist. mkd. T22S R8W S11 BT.
A W.Fir 10" dia., bears N.22°W., 56 lks. dist. mkd. T22S R8W S2 BT.

Fd. OK, April 16, 1975 by Woolley Logging, C.S. File 57/21-7

BLM Corrective Dependent Resurvey by John A. Farmer, March-April 1993 - DCSO records Vol. 51 Pg. 19549.

Found - Iron post with brass cap, properly marked.
A fir, 17" dia., bears N.19°E., 62 lks. dist. with healed blaze.
A fir, 13" dia., bears S.16°E., 137½ lks. dist., with healed blaze. (Record, 139 lks.)
A hemlock, 13" dia., bears S.21°W., 15 lks dist., with healed blaze. (Record, 16 lks.)
A decayed white fir snag, 18" dia., bears N.22°W., 54½ lks. dist., no marks visible. (Record, 56 lks.)
New Bearing Tree -
A fir, 10" dia., bears N.21 3/4°W., 10 lks dist., mkd. T22S R8W S2 BT

BLM remonumentation by Aaron M Graham, Cadastral Surveyor and Michael Jones Surveying Technician under Group #2199 surveyed April 2008/April 2009 - (DCSO rec. Vol. 56 Page(s) 21939-40)

The cor. of secs. 1, 2, 11, and 12, perpetuated by Brooks and Peterson in 1965-67; monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd.
from which the remains of an original bearing tree
A decayed fir stump, 42" dia., bears S.26°E., 58.7 ft., no marks visible.
and the bearing trees mkd. by Brooks and Peterson in 1965-67
A fir, 21" dia., bears N.19°E., 40.9 ft., with a healed blaze.
A fir, 17" dia., bears S.16°E., 90.8 ft., with a healed blaze. (Record, 91.7 ft.)
A roothole, bears S.21°W., 10.6 ft., alongside of which is a down hemlock, 16" dia., with a healed blaze.
and the remains of a bearing tree mkd. by Farmer in 1993
A roothole, bears N.21¾°W., 6.6 ft., onside of which is a down fir, 11" dia., with a healed blaze. continued

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and new bearing trees

A hemlock, 14" dia., bears S.43 $\frac{3}{4}$ °W., 14.2 ft., mkd. T22S R8W S11 BT.

A fir, 19" dia., bears N.25 $\frac{3}{4}$ °W., 23.5 ft., mkd. T22S R8W S2 BT.

The geographic position (NAD 1983 (2007)) of the corner of sections 1, 2, 11, and 12, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43°40'44.56"N. Longitude: 123°36'18.64"W.

Fd. BC & 4 BT by Ron Rice, 7/2014 - C.S. File 65/84-8