

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 609700

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 & 36 only, T21-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO recs Vol. 2 Pgs 835-36)

Set post to section corner between sections 35 & 36, from which:

Fir tree 36" dia., bears N.70°W., 10 lks.

Fir tree 36" dia., bears N.20°E., 20 lks.

Post on top of ridge, course NW & SE.

Post and BTs found by Wm. Wright, GLO survey, Contract #486, dated Aug. 1, 1883 (DCSO records, Vol. 2 Page 838)

GLO resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12544)

Point for the cor. of secs. 35 and 36 only, determined from the original bearing trees:

A Fir 60" dia., bears N.20°E., 20 lks. with blaze healed.

A Fir 53" dia., bears N.70°W., 10 lks. with blaze healed.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 25" in the ground, with brass cap mkd:

T 21 S R 8 W

S 35 | S 36

S 1

T 22 S R 8 W

1952

from which

A Fir 10" dia. bears N.39¼°W., 42 lks. mkd T21S R8W S35 BT

On Sept. 16, 1963, Milo Godfrey, DCSO, found shattered stub only. (probably notation is in C.S. File 52/14 - V.L. 5/95)

Fd. Ok by Gary Smithers - May 2005 - C.S. File 65/54-22

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22050-1)

The cor. of secs. 35 and 36 only, monumented with an iron post, 2" dia., firmly set, projecting 11 ins. above ground, with brass cap mkd.

from which the remains of the original bearing trees

A fir stump, 64" dia., bears N.20°E., 14.9 ft., no marks visible. (Record, 13.2 ft.)

A fir stump, 50" dia., bears N.70°W., 8.8 ft., no marks visible. (Record, 6.6 ft.)

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 609700

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 & 36 only, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a BT mkd. by Lytle, et al., in 1952-54
A decayed fir stump, size indeterminate, bears N.39¼°W.,
28.8 ft., no marks visible. (Record, 27.7 ft.)
and BTs mkd by person(s) unknown reported by Smither, in 2005
A fir, 13" dia., bears N.64½°E., 12.6 ft., with a healed
blaze with a nail and washer in face, and a spike on
the left side center.
A fir, 20" dia., bears S.8¾°E., 30.1 ft., with a healed
blaze with a nail and washer in face, and a spike on
the left side center.
A fir, 9" dia., bears S.79¾°W., 31.2 ft., with a healed
blaze with a nail and washer in face, and a spike on
the right side center.
A fir, 9" dia., bears N.34°W., 13.9 ft., with a healed
blaze with a nail and washer in face, and a spike on
the left side center.
An aluminum fence post is alongside the cor.
Corner falls on a spur, slopes N.40°W.