TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 25 and 36

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1555)

Set ¼ sec. post, from which
A Chittemwood 6" dia., bears N.83°W., 25 lks. dist.
A Maple 10" dia., bears S.27°E., 42 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13681)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 25
S 36
T 22 S R 8 W
1964

from which
A Fir 6" dia., bears N.63½°E., 74½ lks. dist. mkd. ¼ S25 BT.
A Fir 32" dia., bears S.30°W., 161 lks. dist. mkd. ¼ S36 BT.