

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM sec. subdivision by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13719)

Point for the center ¼ sec.cor. of sec. 25, at intersection with the E. and W. center line.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: C ¼ S 25

1964

from which

A Fir 35" dia., bears N.19°E., 35 lks. dist. mkd. C¼ S25 BT.

A Hemlock 36" dia., bears S.78½°W., 16 lks. dist. mkd. C¼ S25 BT.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - P.L. Earle, K. Cheney, crew - Nov. 18, 1975 - C.S. File 57/39-14

Found - BLM 1964 brass cap properly marked. Iron fence post alongside.

A Fir snag 35" dia., bears N.19°E., 23.1 ft., has good blaze, tagged.

A Hemlock snag 37" (Rec. 36") dia., bears S.78½°W., 10.6 ft. scribed "C ¼ S25", tagged.

New BTs -A 10" Hemlock bears N.8°W., 90.9 ft. scribed "C ¼ S25 CS BT", tag.

A 20" Maple bears N.67½°E., 55.1 ft. scribed "C ¼ S25 CS BT", tagged. BT is a double tree, one base. Measurement and bearing are taken to center of base, dia. is on larger (scribed) trunk.

Found OK by C. Sweeden, Aug. 2000 - M135-34