TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1556)

Set ¼ sec. post, from which
A W.Oak 4" dia., bears N.8°W., 39 lks. dist.
A W.Oak 3" dia., bears S.10°E., 27 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13684)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 24
S 25
T 22 S R 8 W
1964

from which
A Fir 6" dia., bears N.36½°E., 78½ lks. dist. mkd. ¼ S24 BT.
A Hemlock 20" dia., bears S.17°W., 71 lks. dist. mkd. ¼ S25 BT.
Cor. falls at top os ascent, slopes N.

Corner found OK - Douglas Co. Surveyors Office, Milo Godfrey, Deputy - 1963 - C.S. File 52/14 - "1964 GLO brass cap & 2 new BTs"

Fd. OK, Dec. 1992 by C. Mulkins, M 116-34