

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1597)

Set Fir post for ¼ sec., from which
A Fir 28" dia., bears South, 103 lks.
A Dogwood 8" dia., bears N.70°E., 31 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Witnesses: N.E. Richardson and Oliver Haines - Dec. 1929 - Vol. 4 Page 4; C.S File 14/38 and M 6-7

Position identified from a Fir, which I judge to be an O.B.T. This tree has been badly burned but carries an axe blaze of proper age, position and shape to have been the orig. BT. Bearing and distance places corner on an E. and W. blazed line.

Set sandstone 4" x 6" x 20" for corner and blaze and scribe
A 14" Hemlock N.32°E., 88 lks. dist. "¼ S1 CS BT".
A 42" Fir S.5°W., 18 lks. dist. "¼ S12 CS BT" in bark.

Douglas Co. Surveyors Office - Milo Godfrey - Dec. 11, 1962 -C.S. File 52/14-134

No trace of orig. or renewals found.

Survey by Les Roberts, L.S. #1039 - For: International Paper Co. - July 2, 1985 - C.S. File 63/18-4(C) and M 90-74

Found - 29" Hemlock N.32°E., 58.1 ft., scar visible.
48" downed Fir, S.05°W., 11.9 ft., bark scribed.
4 x 6 x 20" sandstone set by Irving was not found.
Set 2½" x 30" alum. pipe and cap marked with S-T-R, date and PLS No. 1039. Purple magnetic marker buried under alum. pipe.
Set metal fence post, with land survey monument sign wired to, beside alum. cap.
New BT - 6" Hemlock S.83°E., 9.5 ft., scribed/painted red.
Corner lies about 230 ft. North of E-W ridge.

Fd. BC & 2 BTs by Ron Rice, 7/2014 - C.S. File 65/84-8