

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12544)

Point for the ¼ sec. cor. of sec. 1, at proportionate distance.

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

¼ S 1
1952

from which

A Fir 42" dia., bears S.26½°E., 55 lks. dist. mkd. ¼ S1 BT
A Fir 55" dia., bears S.49½°W., 56 lks. dist. mkd. ¼ S1 BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, crew - Sept. 1963 - C.S. File 52/14-26

Found - Brass cap set in 1952.

42" D.Fir S.26½°E., 36.3 ft., very plain axe blaze visible.

55" Fir S.49½°W., 37.0 ft. is uprooted and down.

New BT - 38" D.Fir N.52°E., 22.5 ft. mkd. ¼ S1 CS BT.

No other tree available south of line.

Gary Smithers - May 2005 - C.S. File 65/54-20

Found - 1952 Brass Cap on Iron Pipe firmly set.

50" Fir, S.26°E., 36.3 ft., with healed face and BT tag. OBT

55" Fir, S.49°W., 37.0 ft., uprooted and down.

48" Fir, N.52°E., 22.5 ft., with healed face and BT tag. OBT

Set - 6 foot Steel Post 1.8 feet North of the Brass Cap

New BTs- 10" D.Fir, S.30°W., 7.7 feet to spike driven in side center, marked "T22 R8 ¼ S1 BT", with BT tag.

9" D.Fir, S.45°E., 16.8 ft. to spike driven in side center, marked "T22 R8 ¼ S1 BT", with BT tag.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22049)

The ¼ sec. cor. of sec. 1 only, on the N. bdy. of T22S R8W., monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd by Lytle, in 1952-54
continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 50" dia., bears S.26½°E., 36.3 ft., with a healed blaze.

A roothole bears S.49½°W., 37.0 ft., with a down fir, 54" dia., alongside with axe marks on loose bark. and a BT mkd. by Milo Godfrey, in 1963

A fir, 49" dia., bears N.53°E., 22.2 ft., with a healed blaze. and BTs mkd. by Smither, in 2005

A fir, 9" dia., bears S.46°E., 16.7 ft., with scribe marks T22 R8 ¼ S1 BT visible on pitched-over partially healed blaze, and a spike on the left side center.

A fir, 10" dia., bears S.30°W., 7.7 ft., with scribe marks T22 R8 ¼ S1 BT visible on pitched-over partially healed blaze, and a spike on the left side center.

An aluminum fence post is alongside the cor.
Corner is located 3 ft. downhill from the down Lytle SW BT.