

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 644700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only, T21-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 2 Page(s) 835)

-----  
Set Fir post, for ¼ sec. corner, from which  
    Fir tree, 40" dia., bears N.40°E., 25 lks.  
    Fir tree, 50" dia., bears S.60°E., 38 lks.

GLO resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron; & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12543)

-----  
Point for the ¼ sec. cor. of sec. 36 only, determined from the remains of the original bearing trees:

    A Fir 70" dia., bears N.40°E., 25 lks. dist., scribed ¼ S BT on bark.

    A stump hole of a large fallen Fir, bears S.60°E., 38 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, with brass cap mkd:

¼ S 36  
    1952

from which

    A Fir 52" dia., bears N.7°E., 46 lks. dist. mkd. ¼ S36 BT.

    A Hemlock 7" dia., bears N.74°45'E. 57 lks. mkd. ¼ S36 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, crew - Sept. 1963 - C.S. File 52/14-30

-----  
Found - Brass cap set in 1952.

    Sawed stump of 52" Fir, N.7°E., 30.4 ft., shows good scar.

    Burned shell of 70" Fir N.40°E., 16.5 ft. No marks remain.

    No trace of 7" hemlock mkd. in 1952.

New BT - 9" Maple N.37°E., 78.2 ft. mkd. ¼ S36 CS BT.

    No other trees available.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20735)

-----  
The ¼ sec. cor. of sec. 36 only, on the S. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

continued next page

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree  
A fir stump, size indeterminate, bears N.40°E., 16.5 ft.,  
no marks visible.  
and a bearing tree mkd. by Lytle, et. all  
A fir stump, 50" dia., bears N.7°E., 30.4 ft., with scribe  
marks ¼S 36 BT visible on open blaze.  
and new bearing trees  
A fir, 16" dia., bears N.69½°E., 47.1 ft., mkd. ¼ S36 BT.  
A fir, 7" dia., bears N.39°W., 10.6 ft., mkd. X BT.

Gary Smithers - May 2005 - C.S. File 65/54-21  
-----

Found - 1952 Brass Cap on Iron Pipe firmly set.  
70" Fir stump, N.40°E., 16.5 ft., rotted with no  
markings. OBT  
54" Fir stump, N.70°E., 30.4 ft., with visible  
scribes and bearing tree tag. OBT  
21" Maple, N.37°E., 78.2 ft, with healed face and BT  
tag. OBT  
17" D. Fir, N.69°E., 47.1 ft. to spike side center,  
with healed face and BT tag. 2000  
8" D. Fir, N.39°W., 19.6 ft. to spike side center,  
with healed face and bearing tree tag. 2000  
New BT - 18" Fir, S.52°E., 8.8 ft. to spike set side center,  
scribed "T21 R8 ¼ S36 BT", with BT tag.  
Set - 6 foot Steel Post alongside.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor,  
under Group #2115, surveyed January/May 2007 (DCSO records  
Vol. 56 Page(s) 22047-8)  
-----

The ¼ sec. cor. of sec. 36 only, monumented with an iron  
post, 1" dia., firmly set, projecting 4" above ground, with  
brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A burned and decayed fir stump, size indeterminate, bears  
N.40°E., 19.0 ft., no marks visible. (Record, 16.5 ft.)  
and the remains of a BT mkd. by Lytle, et al., in 1952-54  
A burned fir stump, 50" dia., bears N.7°E., 30.4 ft., with  
scribe marks ¼ S36 BT visible on detached face.  
and a BT mkd. by Milo Godfrey, in 1963  
The northeasterly and largest of a clump of three maples,  
21" dia., bears N.39°E., 78.1 ft., no marks visible.  
and bearing trees mkd. by Graham in 1999-2000  
A fir, 17" dia., bears N.69½°E., 47.1 ft., with illegible  
scribe marks visible on partially healed blaze.

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 644700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only, T21-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 9" dia., bears N.41°W., 19.6 ft., with axe marks X at breast height and a healed blaze. (Record, N.39°W., 10.6 ft.)  
and a BT mkd. by Gary T. Smither, in 2005  
A fir, 19" dia., bears S.50½°E., 9.1 ft., with illegible scribe marks visible on pitched-over partially healed blaze.