

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T22-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1500)

Set post cor. of secs. 19, 24, 25 and 30, from which
A Fir 36" dia., bears N.49°E., 60 lks. dist.
A Fir 30" dia., bears S.30½°E., 56 lks. dist.
A Fir 30" dia., bears N.11°W., 70 lks. dist.
A Fir 36" dia., bears S.26°W. 170 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13676-77)

The sec. cor., determined at record bearing and distance from the remaining bearing trees:

A sawed Fir stump 60" dia., bears N.49°E., 60 lks. dist. with fragmentary scribe marks visible on opened blaze.
A burned and decayed Fir stump, size indeterminate, bears S.26°W., 170 lks. dist. with no marks remaining.
A sawed Fir stump 42" dia., bears N.11°W., 70 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S
R8W R7W
S 24 S 19
S 25 S 30
1963

from which new bearing trees

A Fir 6" dia., bears N.75 3/4°E., 56 lks. dist. mkd. T22S R7W S19 BT.
A Fir 9" dia., bears S.10¼°E., 31 lks. dist. mkd. T22S R7W S30 BT.
A Fir 10" dia., bears S.23½°W., 53½ lks. dist. mkd. T22S R8W S25 BT.
A Fir 5" dia., bears N.78°W., 36½ lks. dist. mkd. T22S R8W S24 BT.

Cor. falls at W. edge of a skid road, 15 lks. wide, bears N.25°W. and S.20°E.

Cor. tied in BLM resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #928, surveyed July/Aug. 1977 (DCSO records, Vol. 40 Pages 16017-18)

Fd. OK by C. Sweeden, Oct. 1999 - M133-33