

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T22-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1501)

-----  
Set post cor. of secs. 1, 6, 7 and 12, from which  
A Fir 12" dia., bears N.38°E., 41 lks. dist.  
A Fir 12" dia., bears N.15°W., 24 lks. dist.  
A Fir 50" dia., bears S.42°W., 35 lks. dist.  
A Fir 36" dia., bears S.42°E., 42 lks. dist.

Fd. OK, Jan. 1881 by W.H. Byars, GLO survey, Contract #376 (DCSO records, Vol. 4 Page 1533-34)

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson and Oliver Haines - Dec. 1929 - C.S. File 14/38 and M 6-7

-----  
Identified location from 4 O.B.T.s which I reblazed and scribed.  
Set a sandstone 7" x 12" x 28" for corner with an X chiseled on top, 12 CS on SW. face; 1 on NW. face.; 6 on NE. face and 7 on SE face.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-124

-----  
Found - Rock set by Irving in 1929. Rock had fallen over but apparently had not slid away from corner. Reset rock and pile mound of rock around it.  
32" Fir N.15°W., 15.8 ft. good bark scribing visible. Blaze and scribe "BT" in wood.  
48" Fir S.42°E., 27.7 ft. good bark scribing visible. Blaze and scribe "BT" in wood, top of tree now dead.  
60" dead Fir S.42°W., 23.1 ft. good bark scribing visible. Blaze and scribe "BT" in wood.  
No trace found of NE BT.  
Blaze and scribe:  
16" Hemlock N.39°E., 48.7 ft. mkd. T22S R7W S6 CS BT.  
No live trees available in SW.  
Corner lies on very steep NE slope approx. 300 ft. North of top of ridge.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14410-11)

-----  
(Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T22-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

The Sec. cor., perpetuated and recorded by Irving in 1929, monumented with a sandstone, 30 x 15 x 8 ins., firmly set 18" in the ground, mkd. X on the top, 1 on NW.; 6 on NE.; 7 on SE.; and 12 CS on SW. face, from which the original bearing trees:

A Fir 45" dia., bears S.48°E., 42 lks. dist. with scribe marks T22S R7W S7 CS BT visible on the bark. (Rec. bearing S.42°E.)

A Fir snag 63" dia., bears S.42°W., 30 lks. dist. with scribe marks S12 T22S R8W visible on the bark. (Rec. dist. 35 lks.)

A Fir 38" dia., bears N.5°W., 24 lks. dist. with healed blaze. (Rec. bearing N.15°W.)

and a bearing tree mkd. by Godfrey in 1962

A Hemlock 16" dia., bears N.40°E., 75 lks. dist. with fragmentary scribe marks visible on open double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S	
R 8 W	R 7 W
S 1	S 6
S 12	S 7
1968	

from which

A Hemlock 5" dia., bears S.22°E., 21 lks. dist. mkd. T22S R7W S7 BT.

Deposit the corner stone alongside the iron post.

Fd. OK, July 1985, Les Roberts, M 90-74 & C.S. 63/18-4(F)