

PRIMARY CORNER DESCRIPTION NE Cor. Samuel Rich DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated Sept. 1856

N.E. Cor. Claim 38 in river.
Set witness post 287 lks. N. on right bank of river, from
which,
 A Fir 15" dia., bears N.5°E., 56 lks.
 A Fir 15" dia., bears S.80°W., 43 lks.

(West on N. bdy. of Claim 38)
From witness cor. offset W. 1.66 chs. and South 2.87 chs.
Set witness cor. between two perpendicular rocks about 6 ft.
apart. The one on the S. being about 10 ft. high and the
other about 20 ft.
 A Fir 40" dia., bears S.55°E., 60 lks.

GLO retracement of Donation Land Claims, by George S.
Pershin, under Special Instructions - Date of contract, July
25, 1896

The witness cor. of NE. cor. of Claim 38 (W.C. N. on right
bank of river)
At this corner, I find the post missing but both witness
trees are standing viz.
 A Fir 15" now 30" dia., S.80°W., 43 lks. dist., markings
 all grown over which I cut away and find the letters
 perfectly distinct on the sound solid wood.
 The other tree, a Fir 15" now 24" dia. N.5°E., 50 lks.
 dist. is dead and all the markings are burned or
 decayed.
From the green tree, I measure N.80°E., 43 lks. and Set a
sandstone 15 x 10 x 8 ins., 10" in the ground for witness
cor. of claim 38, marked W C Cl. 38.

(W.C. on N. bdy. West of true cor. point)
On account of the high water in the river, the location of
the witness cor. on the north bdy. is covered with water.
The two rocks are still at place. There must be a mistake
about the bearing tree as S.55°E., 60 lks. dist. would be out
in the river.

Survey for Albert Hess and John N. Hedden - July 25, 1899 -
Vol. 2 Page 78

I find my flag tree to be the bearing tree to the witness
cor. of the NE cor. of S. Rich's claim. Reset said corner by
setting a stone and raising a mound of stone.

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 038010

PRIMARY CORNER DESCRIPTION NE. Cor. Samuel Rich DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley, under Group # 709, surveyed May/Sept. 1970 (DCSO records Vol. 36 Page(s) 14906-07)

(W.C. on N. bdy. West of true cor. point)
The witness cor. for the NE. cor. of DLC #38, determined from original calls of the record:

A sandstone bluff 20 ft. long, 20 ft. high, faces S., bears North, 4½ lks. dist.

The depression from which a sandstone boulder, 10 x 8 x 5 ft. has been dislodged, bears South, 4½ lks. dist., the boulder now bears South 15 lks. dist.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 6" in the ground, to solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd:

W C
T 22 S R 9 W
S 8
C 38
1970

from which new bearing objects

A sandstone bluff 20 ft. long, 20 ft. high, faces S., bears N.51¼°W., 6½ lks. dist. mkd. X BO. This is same bluff as recorded in original survey.

A sandstone boulder, 6 x 5 x 4 ft. above ground, bears S.21½°E., 8½ lks. dist., mkd. X BO.

1970 brass cap and bearing objects Fd. OK, March 1986 by L. Olson - M 100-65

Note - W.C. is S.89°51'25"W., 108.82 ft of orig. position.

Found OK by T. Rambo, Aug. 1999 - M133-15

Fd. BC 2002 M159-2 by Kris DeGroot