

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T22-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 274 survey dated Sept. 10, 1877 (DCSO records Vol. 4 Page(s) 1647)

-----

Set a Fir post 5" dia., on steep, rocky point. Made rock mound, 12" high, for corner to secs. 25, 30, 31 and 36, from which

- A Fir 20" dia., bears N.1°E., 67 lks. dist.
- A Fir 10" dia., bears N.40°W., 24 lks. dist.
- A Fir 16" dia., bears S.25°E., 135 lks. dist. (estimated)
- A Fir 16" dia., bears S.35½°W., 40 lks. dist. (estimated)

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1717)

-----

The Sec. cor., which is a post 2 ft. above ground, 4" sq. on point of hill sloping SW., marked T22S S30 on the NE.; R9W S31 on the SE.; R10W S36 on the SW.; and S25 on the NW. faces with 1 notch on the S. and 5 notches on the N. edges, from which

- A Fir 20" dia., bears N.1°E., 67 lks. dist. mkd. T22S R9W S30 BT.
- A Fir 18" dia., bears S.25°E., 35 lks. dist., marks grown over.
- A Fir 20" dia., bears S.34°W., 41 lks. dist., marks grown over.
- A Fir 14" dia., bears N.40°W., 24 lks. dist. mkd. T22S R10W S25 BT.

Practically agreeing with notes furnished me by the U.S. Surveyor General.

Douglas County Surveyors Office - James W. Byron, Surveyor - C.S. File 54/60-26 - Jan. 9, 1968

-----

Corner searched for, not found. Fd. only one possible BT - no scribe.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed April/June 1982 - (DCSO records Vol. 36 Page(s) 14841-42)

-----

The cor. of secs. 25, 30, 31 and 36, determined at record bearing and distance from the remaining original bearing tree:

(Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. cor. for 30 & 31; 25 & 36, T22-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 22" dia., bears S.35°W., 40 lks. dist. with fragmentary scribe marks visible on open and burned blaze. (Rec. estimated 40 lks.)

At the corner point

Seat a brass tablet 3¼" dia., 3½" stem, in drill hole, in solid rock, with top mkd:

T 22 S	
R 10 W	R 9 W
<u>S 25</u>	<u>S 30</u>
S 36	S 31
1970	

from which reference monuments and bearing objects

A brass tablet, 3¼" dia., 3½" stem, in a drill hole, in solid rock, for a reference monument, bears N.88 3/4°E., 7 lks. dist. with top mkd. T22S R9W RM 1970 and an arrow pointing to the corner.

A rock ledge bears S.2½°E., 21 lks. dist. mkd. X BO.

A brass tablet, 3¼" dia., 3½" stem, in a drill hole, in solid rock, for a reference monument, bears S.49¼°W., 7 lks. dist. with top mkd. T22S R10W S36 RM 1970 and an arrow pointing to the corner.

Same rock ledge bears N.46°W., 23½ lks. dist. mkd. X BO.  
The corner is located on the point of large rock outcrop.