

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T22-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 274 survey dated Sept. 10, 1877 (DCSO records Vol. 4 Page(s) 1646-47)

Set a Fir post 48" long, 5" dia., 20" in ground, for corner to secs. 19, 24, 25 and 30, from which
A Yew 10" dia., bears N.80°E., 20 lks. dist.
A Yew 12" dia., bears S.85°E., 25 lks. dist.
A Fir 48" dia., bears S.40°W., 127 lks. dist.
A Yew 16" dia., bears N.54°W., 36 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #718, surveyed June/Aug. 1970 - (DCSO records Vol. 36 Page(s) 14842-43)

Point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
T 22 S
R 10 W R 9 W
S 24 S 19
S 25 S 30
1970

from which
A Hemlock 43" dia., bears N.62½°E., 61½ lks. dist. mkd. T22S R9W S19 BT.
A Hemlock 45" dia., bears S.56°E., 50 lks. dist. mkd. T22S R9W S30 BT.
A Hemlock 36" dia., bears S.78¼°W., 74 lks. dist. mkd. T22S R10W S25 BT.
A Hemlock 19" dia., bears N.36°W., 68 lks. dist. mkd. T22S R10W S24 BT.