

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; & 24 of T22-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1629)

-----  
Marked a Fir 6" dia., for the ¼ sec. corner.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 274 survey dated Sept. 10, 1877 (DCSO records Vol. 4 Page(s) 1646)

-----  
Set a Fir post 40" long, 6" dia., 12" in ground, from which  
A Maple 10" dia., bears N.10°E., 49 lks. dist.  
A Chinquapin 6" dia., bears N.52°W., 37 lks. dist.  
(This line was compelled to be run in order to re-establish this corner, as a fire had destroyed the old corner.)

Survey by Eugene Wobbe - For: International Paper Co. - June 15, 1983 - M 94-51

-----  
Set 1" Iron pipe with brass cap mkd. ¼ S19 R9W S24 R10W T22S.  
New BTs -16" Hemlock N.30°W., 9.1 ft.  
18" Hemlock N.63°W., 21.2 ft.