

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 100439

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 13 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1746)

Set a sandstone 16x12x8 ins., 12" in the ground, marked 1/4 S. on W. face for the 1/4 sec. cor. from which
A Fir 36" dia., bears N.1°E., 80 lks. dist. mkd. 1/4 S BT
A Fir 12" dia., bears N.61°W., 22 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - and Crew, - Sept/Oct. 1961 - M 22-16 and C.S. File 52/86

Found - Orig. 12" now 30" R.Fir N.61°W., 18.5 ft., not 14.5 ft. Shows good scar at base and old face above previously opened and partly burned, no scribing found.

Sandstone at corner with chiseled "1/4S" on West face.
Set Brass cap alongside corner stone mkd:

County Surveyors Office

T 22 S

East 1/4 S13

R10W | R9W

1961

New BTs - Rescribed 0BT, 30" R.Fir N.61°W., 18.5 ft. 1/4 S13 CS BT.

9" R.Fir bears N.29°E., 24.7 ft. scribed S18 CS BT.

Fd. OK, July 1989 by R. Stuntzner - M 108-41

Clyde Mulkins - Oct. 31, 1995 - for: I.P. Timbers - M 123-24

Mon. Fd. - Do. Co. Brass cap (mkd. as common 1/4 cor for Secs. 13 & 18.)

Bt's Fd. - 37" D.Fir, with a healed face, bears N.60°W., 18.2'.

16" D.Fir, with a healed face, bears N.30°E., 23.6'.

New BT's - 14" D.Fir, I scribed "T22S R10W 1/4 S13 BT", bears N.6°W., 21.8'.

11" D.Fir, I scribed "T22S R10W S13 BT", bears S.48°W., 21.8'.

Fd. BC by M Heimburger - 5/2021 - M178-34