

PRIMARY CORNER DESCRIPTION W. Sec. cor. for 7 and 18 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1675-76)

I set Cherry post, 4 ft. long, 4" sq., 24" in ground on steep hillside, sloping SW. at the point of intersection for closing corner to secs. 7 and 18, marked C.C. on the E.; T22S S7 on the N.; R9W S18 on the S. sides with 4 grooves on the S. and 2 grooves on the N. sides, from which
A Chinquapin 8" dia., bears N.23°E., 25 lks. dist. mkd. T22S R9W S7 BT.
A Chinquapin 8" dia., bears S.59°30'E., 12 lks. dist. mkd. T22S R9W S18 BT.
A Fir 10" dia., bears N.81°W., 33 lks. dist. mkd. C.C. T22S R9W S7-18 BT.

Survey by Eugene M. Wobbe, LS #1093 - For: International Paper Co. - Feb. 23, 1983 - M 90-41

Set I.P. with brass cap mkd: S7 & S18 T22S R9W.
New BTs -20" Fir bears N.37°E., 26.0 ft.
22" Fir bears N.60°W., 7.4 ft.
14" Fir bears S.44°E., 12.4 ft.

FD. OK - C. Mulkins - Oct. 31, 1995 - M 123-24

Jerry Estabrook - For: Roseburg Resources - 7/2020 - M177-35

Found - A 1½" iron pipe with 2½" brass cap marked "PLS1093 T22S R10W 12 R9W 7 18 1982" per M90-41 with steel post along side.
A 23" Fir with healed face and tag bears N.37°E., 26.0'.
A 16" Fir with healed face and tag bears S.44°E., 12.4'.
A 25" Fir with healed face and tag bears N.60°W., 7.4'.
LAT. and LONG. per GARMIN ETREX hand held GPS:
N: 43°39'53.6" W: 123°49'36.8"