

PRIMARY CORNER DESCRIPTION E. 1/4 for Sec. 1 only, T22-10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1748)

This point falling on a stone in place 16x12, 6" above ground, I mark a cross (X) at exact cor. point with ¼ S on W. face for ¼ sec. cor., from which
A Fir 40" dia., bears S.45°E., 79 lks. dist. mkd. ¼ S BT.
A Fir 30" dia., bears S.3°W., 54 lks. dist. mkd. ¼ S BT.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16027)

The ¼ sec. cor. of sec. 1 only, on the E. bdy. of T22S R10W, monumented with the original sandstone, in place, 20 x 20 x 20 ins. (Rec. 16x12x6), above ground, mkd. ¼ S1 on W. face, and X on top, from which the remaining original bearing tree:
A Fir 67" dia., bears S.45°E., 76 lks. dist. no marks visible on open blaze. (Rec. 79 lks.)
and a bearing tree of which I have no record:
A Fir 54" dia., bears N.64°E., 30 lks. dist. no marks visible on open blaze.

At the corner point
Set a brass tablet 3¼" dia., 3½" stem, in a drill hole, flush with the sandstone boulder, with top mkd:
T 22 S
R 10 W
¼
S 1
1974

from which new bearing trees:
A Fir 16" dia., bears S.13°W., 58 lks. dist. mkd. ¼ S1 BT.
A Fir 22" dia., bears N.35°W., 26 lks. dist. mkd. ¼ S1 BT.

Cor. Fd. and used in BLM resurvey by Malloy and Farnsworth, under Group #'s 1125 and 1226, surveyed Nov/Dec. 1982 - (DCSO records, Vol. 47 Page 17935)