

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17943-44)

-----  
The point for the ¼ sec. cor. of sec. 6 only, T22S R9W, at proportionate dist., on the W. bdy. of sec. 6.  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:  
                          T 22 S  
                          R 10 W | R 9 W  
                                  | ¼ S 6  
                                  1963

from which  
  A Fir 28" dia., bears N.58°E., 34½ lks. dist. mkd. X BT.  
  A Fir 22" dia., bears S.31½°E., 52 lks. dist. mkd. ¼ S6 BT.

Survey by Steven P. Ness - LS #811 - June 26, 1992 - C.S. File 63/138-13

-----  
Found - No trace of monument.  
      22" D.Fir stump 3½ ft. tall, S.27°E., 34.3 ft. (Rec. S.31½°E.), bark removed, sheet metal cap on top.  
      30" D.Fir stump 2½ ft. tall, N.60°E., 22.8 ft. (Rec. N.58°E.), bark removed, sheet metal cap on top.  
Set 30" x 2¼" Iron post with 2½" brass cap, top 5" above mound of stone at intersection of record distances from found accessories. Cap mkd:  
                          T 22 S  
                          R 10 W | R 9 W  
                                  | ¼ S 6  
                                  1992 RPLS 811

No new accessories marked.  
Corner is located in a newly logged BLM clear-cut (Mill Creek Ridge timber sale Unit #4) It is on very steep (80%) southwest slope about 400 ft. NE of Little Mill Creek.