

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1679)

Set Alder post 4½ ft. long, 4" sq., 24" in the ground on hill side sloping SE for ¼ sec. corner mkd. ¼ S. on the N. face, from which,
A Fir 36" dia., bears N.77°E., 88 lks. dist. mkd. ¼ S BT.
An Alder 5" dia., bears S.4°E., 33 lks. dist. mkd. ¼ S BT

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17942)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S R 9 W
¼ S 6
 S 7
 1982

from which
A Fir 26" dia., bears N.80 3/4°E., 56½ lks. dist. mkd. ¼ S6 BT.
A Fir 30" dia., bears S.14½°E., 27 lks. dist. mkd. ¼ S7 BT

David Edwards - For: Roseburg Resources - 8/2025 - M186-25

Found - 34" Fir with healed blaze. S.14½°E. 17.8'
Gone - Fir N.80¾°E.
New - 18" Fir scribed "¼ S6 BT" N.18°W. 50.0' 5.5' steel posts set 2' N.1°W. on line and 2' east.