

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 140640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM section subdivision by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17944)

Point for the center ¼ sec. cor. of sec. 6 at intersection with the E. and W. center line.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: T 22 S R 9 W

C ¼ S 6
1982

from which

A Cedar 20" dia., bears S.32¼°W., 17 lks. dist. mkd. C ¼ S6 BT.

A Fir 48" dia., bears N.76°W., 42 lks. dist. mkd. C ¼ S6 BT.

Corner is located at bottom of descent, slopes E.

David Edwards - For: Roseburg Resources - 8/2025 - M186-25

Found - 29" Fir, healed blaze. Bears S.32¼°W. 11.2'
52" dead fir bears N.76°W. 27.7'

New - 10" fir scribed "C ¼ S6 BT" bears S.30°W. 14.7'
5.5' steel posts set 2' N.1°W. And S.1°E. on line.