TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 143700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 31 only, T21-9

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 901)

Set Alder post, 4½ ft. long, 5" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on the N. face, from which

An Alder 4" dia., bears S.35 3/4°E., 20 lks. dist. mkd. ¼ S BT.

A Fir 16" dia., bears N.6°30'W., 267 lks. dist. mkd. ¼ S BT.

BLM resuvey by Harvey Woofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16030)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 21 S R 9 W
¼ S 31
1974

from which

A Fir 30" dia., bears N.74¼°E., 78 lks. dist. mkd. S31 BT.

A Fir 22" dia., bears N.55½°E., 140 lks. dist. mkd. ¼ S31 BT.