

PRIMARY CORNER DESCRIPTION Sec. cor. for 17, 18, 19 and 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1639)

Set Maple post 45" long, 5" dia., 20" in ground. Sets in dry ravine, for corner to secs. 17, 18, 19 and 20, from which,
A Maple 14" dia., bears N.40°E., 40 lks. dist.
A Maple 12" dia., bears S.55°E., 77 lks. dist.
A Fir 31" dia., bears S.30°W., 45 lks. dist.
A Maple 16" dia., bears N.25°W., 33 lks. dist.

GL0 survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1719-20)

The Sec. cor., which is a post, 2 ft. above ground, 4" sq., mkd. T22S S17 on the NE.; R9W S20 on the SE.; S19 on the SW.; and S18 on the NW. faces with 3 notches on the S. and 5 notches on the E. edges, from which,
A Maple 16" dia., bears N.40°E., 41 lks. dist. mkd. T22S R9W S17 BT.
A Maple 14" dia., bears S.55°E., 75 lks. dist. mkd. T22S R9W S20 BT.
A Fir 32" dia., bears S.30°W., 45 lks. dist. mkd. T22S R9W S19 BT.
A Maple 20" dia., bears N.25°W., 33 lks. dist. mkd. T22S R9W S18 BT.
Practically agreeing with notes furnished me by the U.S. Surveyor General.

Wilford N. Haines - For: Charles Meade - Done Nov. 12, 1958 - Filed Jan. 15, 1959 - M 13-63

Found - 31" Fir stump with scribe, S.30°W., 45 lks.
Scribed - 12" Maple N.58°E., 25.0 ft.
10" Fir N.77°30'W., 42.1 ft.
Drove 1" x 1" x 36" Iron rod, attached brass cap inscribed "Wilford N. Haines, Survey Pt. #239"

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; A. Bilow - Sept. 1958 - C.S. File 49/103-2

Found - Orig. 31" now 44" Fir stump previously opened, shows good scribing "W".
Clump of Maples checks bearing and distance for NE BT.
No other orig. BTs found.
(Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>I find Haines 1" Iron at corner with 1" stamped cap #239. 16" Maple bears N.59°E., 24.3 ft. T22S R9W S17 BT. (Haines BT) 10" R.Fir bears N.75°W., 42.3 ft. T22S R9W S18 BT. (Haines BT)</p>
<p>Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - & Vernon "Ray" Tracy, crew - June 1962 - C.S. File 49/103-4 ----- Found - "T" Iron and cap at corner. Both trees mkd. by Haines and found by Byron, 1958, still in good condition: 16" Maple N.58°E., 24.3 ft. 10" D.Fir N.77½°W., 42.3 ft. New BTs -13" Alder S.31°E., 57.8 ft. mkd. S20 CS BT. 12" Alder S.53°W., 18.2 ft. mkd. S19 CS BT.</p>
<p>BLM resurvey by James E. Jelley, under Group # 709, surveyed May/Sept. 1970 (DCSO records Vol. 36 Page(s) 14900-01) ----- The Sec. cor., perpetuated and recorded by the county surveyor in 1961, monumented with an iron bar, ½" dia., firmly set, projecting 6" above ground, from which the remaining original bearing tree: A Fir stump 54" dia., bears S.30°W., 45 lks. dist. with partial scribe marks visible on open blaze. and bearing trees mkd. by the county in 1961: A Maple 18" dia., bears N.57°E., 37 lks. dist. with partial scribe marks visible on open blaze. An Alder 15" dia., bears S.33°E., 88½ lks. dist. with partial scribe marks visible on open blaze. An Alder 13" dia., bears S.58°W., 26 lks. dist. with partial scribe marks visible on open blaze. A Fir 15" dia., bears N.77½°W., 65 lks. dist. with healed blaze. At the corner point Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd: T 22 S R 9 W S 18 S 17 S 19 S 20 1970 Deposit the iron bar alongside the iron post.</p>
<p>Fd. OK, March 1978, by Ronald Stuntzner, M 69-36</p>
<p>2</p>