

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1639)

Set a sandstone 16 x 12 x 6, 18" in ground. Made stone mound, for the 1/4 sec. corner. No witness trees.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1719)

After diligent search, could not find the 1/4 sec. corner.

BLM resurvey by James E. Jelley, under Group # 709, surveyed May/Sept. 1970 (DCSO records Vol. 36 Page(s) 14902)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4
S 18 S 17
T 22 S R 9 W
1970

from which

A Fir 22" dia., bears S.72 1/2°E., 100 lks. dist. mkd. 1/4 S17 BT.

A Fir 25" dia., bears N.27 3/4°W., 38 lks. dist. mkd. 1/4 S18 BT.

Fd. OK, March 1978 by Ronald Stuntzner, M 69-36