

PRIMARY CORNER DESCRIPTION Sec. cor for 7, 8, 17 and 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page 1640)

 Set a Maple post 36" long, 5" dia., 12" in ground, for corner to secs. 7, 8, 17 and 18, from which,
 A Fir 60" dia., bears N.22°E., 19 lks. dist.
 A Fir 72" dia., bears S.65°E., 46 lks. dist.
 A Maple 24" dia., bears S.40°W., 16 lks. dist.
 A Maple 30" dia., bears N.10°W., 50 lks. dist.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1673-74)

 The Sec. cor., which is a post, 4" sq., 30" above ground, mkd. T22S S8 on the NE.; R9W S17 on the SE.; S18 on the SW.; and S1 on the NW. faces with 4 notches on the S. and 5 notches on the E. edge, from which,
 A W.Fir 36" dia., bears N.22°E., 19 lks. dist. mkd. T22S R9W S8 BT.
 A Fir 70" dia., bears S.65°E., 46 lks. dist. mkd. T22S R9W S17 BT.
 A Maple 24" dia., bears S.40°W., 16 lks. dist. mkd. T22S R9W S18 BT.
 A Maple 24" dia., bears N.10°W., 50 lks. dist. mkd. T22S R9W S7 BT.

BLM resurvey by James E. Jelley, under Group # 709, surveyed May/Sept. 1970 (DCSO records Vol. 36 Page(s) 14903)

 The point for the sec. cor., determined at a point 4.80 chs. North and 17.05 chs. West from the SE. corner of DLC #38, based upon the official record of the retracement and resurvey by George S. Pershin, Deputy Surveyor in 1896. This point is harmoniously related to items of topography based on Pershin's retracement fo section lines, North and West.
 Set an iron post, 28" long 2½" dia., 24" in the ground, with brass cap mkd:

T	22	S	R	9	W
		S	7	S	8
		S	18	S	17
					1970

from which
 A Fir 15" dia., bears N.83½°E., 118 lks. dist. mkd. T22S R9W S8 BT.
 A Fir 23" dia., bears S.56°E., 102 lks. dist. mkd. T22S R9W S17 BT.
 A Fir 12" dia., bears S.48½°W., 73 lks. dist. mkd. T22S R9W S18 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 7, 8, 17 and 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>A Fir 15" dia., bears N.54½°W., 67 lks. dist. mkd. T22S R9W S7 BT. Deposit broken brown glass at the base of the iron post. Corner falls 20 lks. W. of a graveled road, 20 lks. wide, bearing N.40°E. and S.40°W.</p>
<p>Fd. OK, March 1978, by Ronald Stuntzner, M 69-36</p>
<p>Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - June 10, 1992 - C.S. File 64/26-17 ----- Found - 3¼" BLM brass cap on a 2½" O.E. Iron pipe, leaning 1 ft. West. BC/IP 1 ft. under ground. 15" now 18" dia., 2 ft. tall D.Fir stump with a fully healed single blaze, bears N.83½°E. 77.9 ft 23" now 24" dia., 3 ft. tall D.Fir stump with a fully healed single blaze, bears S.56°E., 67.3 ft 12" now 24" dia., 1 ft. tall D.Fir stump. We opened blaze & found scribing "W" bears S.48½°W. 48.2 ft 15" now 24" dia., 3 ft. tall D.Fir stump with a fully healed single blaze, bears N.54½°W. 44.2 ft 5/8" I.Rod from M 69-36, we agree with record dist. of 327.6 ft. Bearings not checked. Set BLM brass cap, iron pipe, returned to plumb position, 1 ft. below ground. New Accessories: 9" "+" chiseled in sandstone cut bank, 3 ft. above road, along East side of gravel road, bears S.87½°E., 41.9 ft. 6" "+" chiseled in sandstone cut bank, 2 ft. above road, along East side of gravel road, bears S.27°E. 38.6 ft. Metal witness post and sign 4 ft. East of corner. Area around corner is clearcut. No reasonable trees to scribe.</p>
<p>Found OK by T. Rambo, Aug. 1999 - M133-15</p>
<p>Douglas Co. Surveyors Office - Stephen J. Flause - Bill Bohme - 6/23/2010 - C.S. File 67/31-11 ----- Found - 1970 BLM BC/IP 2 ft. under ground. Road work in area possibly contributed to more fill on top of BC/IP 9" chiseled "+" bears S.87½°E., 41.9 ft. (1992) 6" chiseled "+" bears S.27°E., 38.6 ft. (1992) Other BT stumps and B.O. noted in 1992 renewal not checked as they are hidden by dense forest & undergrowth. continued next page</p>

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. cor for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - 5/8" by 30" long IR with 1½" dia., alum. cap. Plumb
over top of FD. BLM BC/IP, protrudes 6" out of
ground. Cap stamped: DOUGLAS CO. SURVEYOR

7 | 8
18 | 17

New - 6" dia., D.Fir, double blazed & scribed "X CS BT" bears
N.57½°W., 6.2 ft.

8" dia., D.Fir double blazed & scribed "T22S R9W S18 CS
BT" bears S.55½°W., 9.9 ft.

Dec. 16½°E