

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1677-78)

Set Fir post 4½ ft. long, 4" sq., 24" in the grund for cor. to secs. 5, 6, 7 and 8, marked T22S S5 on the NE.; R9W S8 on the SE.; S7 on the SW.; and S6 on the NW. faces with 5 notches on the S. and E. edges, from which,
A Fir 6" dia., bears N.59°15'E., 66 lks. dist. mkd. T22S R9W S5 BT.
A Fir 8" dia., bears S.59°30'E., 48 lks. dist. mkd. T22S R9W S8 BT.
A Fir 10" dia., bears S.56°W., 57 lks. dist. mkd. T22S R9W S7 BT.
A Fir 24" dia., bears N.54°30'W., 171 lks. dist. mkd. T22S R9W S6 BT.

BLM resurvey by James E. Jelley, under Group # 709, surveyed May/Sept. 1970, - (DCSO Records, Vol. 36 Pages 14907-08)

The cor. of secs. 6 and 7 only, on the W. bdy. of sec. 8, determined at record distance from the original bearing trees:
A Fir stump 20" dia., bears N.57°E., 66 lks. dist., with healed blaze. (Rec. N.59¼°E.)
A decayed Fir stump 22" dia., bears S.65°E., 48 lks. dist. with no marks visible. (Rec. S.59½°E.)
A Fir 35" dia., bears S.58°W., 57 lks. dist. with a healed blaze and scribe marks CS visible on bark blaze. (Rec. S.56°W.)
A root hole bears N.54½°W., 171 lks. dist. with a down Fir alongside 44" dia., with no marks visible on open blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S R 9 W
 S 6
 S 7 S 8
 1970

and bearing trees mkd. by persons unknown
A Fir stump 19" dia., bears N.60½°E., 16 lks. dist. with partial scribe marks visible on bark blaze.
A Fir 13" dia., bears S.80½°W., 29 lks. dist. with healed blaze.
and a new bearing tree,
A Fir 13" dia., bears N.50½°W., 39 lks. dist. mkd. T22S R9W S6 BT.

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 7 (SE Cor. Sec. 6)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Cor. Fd. and used in BLM resurvey by Wofford, Rogers and Chatters, under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - Vol. 40 Pages 16060-61)

Cor. Fd. and used in BLM resurvey by Malloy and Farnsworth, under Group #'s 1125 and 1226 - surveyed Nov/Dec. 1982 - (DCSO records, Vol. 47 Pages 17929-30)

Survey by Lawrence B. Olsen, PLS #655 - For: International Paper Co. - March 14, 1986 - M 100-65

Found - 1970 BLM brass cap.
18" Fir bears N.50°30'W., 39 lks.
40" Fir S.65°W., 36.5 lks.
Set a steel fence post 1 ft. South of corner.

Found OK by T. Rambo, Aug. 1999 - M133-15