

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 6 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1681)

-----  
Set sandstone 12 x 10 x 6 ins., 9" in the ground on steep hillside sloping SE., for 1/4 sec. corner marked 1/4 on the W. face, from which,  
A Fir 10" dia., bears S.73°E., 18 lks. dist. mkd. 1/4 S BT  
An Alder 10" dia., bears N.62°W., 37 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16062)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd:  
T 22 S R 9 W  
1/4 S 6  
1974

from which  
A Fir 28" dia., bears S.83°W., 89 lks. dist. mkd. 1/4 S6 BT.  
A Fir 30" dia., bears N.79°W., 65 lks. dist. mkd. 1/4 S6 BT.

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17930)

-----  
The 1/4 sec. cor. of sec. 6 only, determined from the remains of an original bearing tree:  
A decayed Fir stump, size indeterminate, bears S.73°E., 18 lks. dist. with scribe marks 4 S visible on decayed blaze.

From this point, the 1/4 sec. cor. of sec. 6 only, erroneously reestablished by Wofford, etal, 1973-79, bears S.4°E., 0.072 chs. dist., monumented with an iron post 2 1/2" dia., firmly set, in a mound of stone, 3 ft. base to top, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point, RESET the iron post, 28" long, 2 1/2" dia., 4" in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 22 S R 9 W  
¼ S 6  
1983

from which the bearing trees mkd. by Wofford, etal,  
A Fir 23" dia., bears S.78½°W., 89½ lks. dist. with healed  
blaze. (Rec. S.83°W., 89 lks.)  
A Fir 31" dia., bears N.85¼°W., 63½ lks. dist. with healed  
blaze. (Rec. N.79°W., 65 lks.)

---

Found OK by T. Rambo, Aug. 1999 - M133-15