

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for secs. 5 and 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1682)

I set stone 12 x 12 x 8 ins., 9" in ground on steep hillside sloping West at the point of intersection for closing corners to secs. 5 and 6, marked C.C. on the S. with 5 marks on the E. and 1 mark on the W. edges, from which

A Fir 30" dia., bears S.2°E., 307 lks. dist. mkd. T22S R9W S5 BT.

A Fir 30" dia., bears S.27°30'W., 90 lks. dist. mkd. T22S R9W S6 BT.

A Fir 36" dia., bears N.17°W., 65 lks. dist. mkd. T22S R9W S5-6 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - Sept. 29, 1971 - C.S. File 53/66-127

Found - Splintered stump N.17°W., 42.9 ft. scribed found BT. Possible BT, rotten and down, S.27½°W., 59.4 ft. I did not find SE BT.

Call on creek (draw) of 313.5 ft. from 31|32 or 106 ft. from 6|5 hits good.

Set brass cap at C.C. mkd: County Surveyors Office

T 21 S R 9 W
S 31
S 6 | S 5
C.C.
1971

New BTs -18" D.Fir S.61°W., 10.6 ft. scribed T22S R9W S6 CC CS BT.

10" D.Fir S.26°E., 17.6 ft. scribed T22S R9W S5 CC CS BT.

BLM resurvey by Harvey Woofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16063-64)

(77.53 chs.)
Intersect the S. bdy. of sec. 31, T21S R9W.
True point for the closing cor. of secs. 5 and 6.
Set an iron post 28" long 2½" dia., 24" in the ground with brass cap mkd: T 21 S R 9 W

S 31
S 6 | S 5
C C
T 22 S R 9 W

(Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for secs. 5 and 6 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

from which

A Fir 23" dia., bears S.38°E., 56 lks. dist. mkd. T22S R9W
S5 CC BT.

A Fir 35" dia., bears S.8½°W., 35 lks. dist. mkd. T22S R9W
S6 CC BT.

(77.73 chs.)

The original closing cor. of secs. 5 and 6, perpetuated and recorded by the County in 1971, monumented with an iron post, 2" dia., firmly set, projecting 4" above ground, with a 1971 county brass cap.

from which the remains of the original bearing trees:

A root hole bears S.2°E., 307 lks. dist. with a down Fir alongside 36" dia., no marks visible on decayed blaze.

A Fir stump 36" dia., bears S.27½°W., 90 lks. dist., no marks visible on decayed blaze.

A Fir stump 36" dia., bears N.17°W., 65 lks. dist. with scribe marks BT visible on open blaze.

and bearing trees mkd. by the County:

A Fir 8½" dia., bears S.26°E., 27 lks. dist. with healed blaze.

A Fir 15" dia., bears S.61°W., 16 lks. dist. with healed blaze.

ADD marks AM 1974 to brass cap.

Both Cors. Fd., tied and used in Corrective Dependent Resurvey by Malloy and Farnsworth, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCS0 records, Vol. 47 Pages 17932-33)

True Cor. point Fd. and used in BLM resurvey by Joel Robb, under Group #1281, surveyed Aug/Oct. 1985 (DCS0 records, Vol. 48 Pages 18190-91)

David Edwards - For: Roseburg Resources - 7/2025 - M186-16

Found - 1977 BLM brass cap.

The 1977 BLM BTs are gone from this point, the 1971 DCS BT's

A 24" dia. Fir bears S.70°E., 8.'

A 30" dia. Fir bears N.49°W., 12.4' both with healed blaze

A 5.5' steel post is set.2 ft S.1°E., on line.