

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Ronald E. Stuntzner - For: International Paper Co.
March 25, 1978 - M 69-36

Set 1½" brass cap with iron pipe at proportionate distance to conform with GLO plat of 1896 by Pershin, which shows the North line of section 17 to jog. I scribe the following BTs:
10" D.Fir bears S.29°W., 10.3 ft.
8" Maple bears N.62°E., 47.1 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 8/14/2002 - C.S. File 66/34-32

Found - 1978 BC/IP not found.
10" now 16" dia., 2½' high D.Fir stump with a fully healed single blaze bears S.29°W., 10.3 ft. (1978)
8" now 12" dia., Maple with a fully healed single blaze, bears N.62°E., 47.1 ft. (1978)
Set - 5/8"x30" long iron rod with DCSO plastic cap in ditch on Westerly side of road flush with ground at a position determined by 1978 BTs.
New - 21" dia., Maple double blazed & scribed "X CS BT" bears S.61°E., 36.7 ft.
Note - Westerly side of road clear cut, no trees available.
1978 D.Fir stump in good shape.
Compass decl. 17¼°E.