

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1678)

-----  
Set Alder post 5 ft. long, 4" sq., 24" in the ground on hillside sloping South, for ¼ S. corner, mkd. ¼ S on the N. face, from which,  
A Fir 48" dia., bears N.52°E., 62 lks. dist. mkd. ¼ S BT.  
A Fir 32" dia., bears S.1°W., 23 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - Vic Cangie, crew - Feb. 6, 1975 - C.S. File 57/17-16

-----  
At the corner point as determined from the remains of the original BTs:

An orig. 48" Fir now a 50" rotten stump which shows a good scar on the bark, bearing N.52°E., 40.9 ft.

An orig. 32" Fir now a 36" rotten stump, previously opened but scribing visible then, has now deteriorated. We open higher and find good scribing "¼", bearing S.9°W., 15.2 ft. (Rec. S.1°W., 15.2 ft.)

WE SET a 1" x 30" Iron pipe with brass cap attached marked:  
County Surveyors Office

T 22 S  
S 5  
S 8 1/4  
R 9 W  
1975

New BTs -An 8" D.Fir bears N.45°W., 34.4 ft. scribed ¼ S5 CS BT.

An 18" D.Fir bears S.74°W., 23.4 ft. scribed ¼ S8 CS BT.

Cor. Fd. and used in BLM resurvey by Malloy and Farnsworth, under Group #'s 1125 and 1226, surveyed Nov/Dec. 1982 - (DCSO records, Vol. 47 Page 17941)

Cor. Fd. and used in BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1281, surveyed Aug/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18197)

Survey by Lawrence B. Olsen, PLS #655 - For: International Paper Co. - March 14, 1986 - M 100-65

-----  
Found - Douglas County brass cap.  
40" Fir stump, S.9°W., 15.2 ft.  
48" Fir stump, N.52°E., 40.9 ft.

(Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

23" Fir S.74°W., 23.4 ft.  
12" Fir N.45°W., 34.4 ft.  
Set a steel fence post 1 ft. North of corner.