

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 240640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM section subdivision by Joel E. Robb, Cadastral Surveyor, under Group #1281, surveyed Aug/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18198)

-----  
Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S R 9 W  
C¼ S 5  
1985

from which

A Fir 58" dia., bears N.40½°E., 227 lks. dist. mkd. C¼ S5  
BT.

A Fir 36" dia., bears N.18°W., 153 lks. dist. mkd. C¼ S5  
BT.

David Edwards For: Roseburg Resources - 7/2025 - M186-16

Found - 60" Fir stump w/metal cap bears N.40½°E. 149.8'

41" Fir stump bears N.18°W 101.0'

New - 14" Fir scribed "C ¼ S5 BT" bears S.1°W. 12.1'

10" Fir scribed "C ¼ S5 BT" bears N.30°W 7.5'

5.5' steel post is set 2 feet N.1°W. on line.