

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias	Description

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1694-95)

Set Maple post 4½ ft. long, 4" sq., 24" in ground on steep hillside sloping SW for corner to secs. 20, 21, 28 and 29, mkd. T22S S21 on the NE.; R9W S28 on the SE.; S29 on the SW. and S20 on the NW. faces with 2 notches on the S. and 4 notches on the E. edges, from which,

- A Fir 10" dia., bears N.8°E., 49 lks. dist. mkd. T22S R9W S21 BT.
- A Fir 20" dia., bears S.8°E., 72 lks. dist. mkd. T22S R9W S28 BT.
- A Fir 24" dia., bears S.71°W., 73 lks. dist. mkd. T22S R9W S29 BT.
- A Fir 14" dia., bears N.52°W., 89 lks. dist. mkd. T22S R9W S20 BT.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16055)

The Sec. cor., perpetuated by person(s) unknown, monumented with a wooden stake, 1" dia., firmly set, projecting 2" above ground, from which the only remaining original bearing tree:

- A Fir 27" dia., bears N.8°E., 49 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 9 W
S 20 S 21
S 29 S 28
1975

from which new bearing trees:

- A Fir 8" dia., bears S.1½°E., 29 lks. dist. mkd. T22S R9W S28 BT.
- A Hemlock 9" dia., bears S.37°W., 36 lks. dist. mkd. T22S R9W S29 BT.
- A Fir 23" dia., bears N.13½°W., 144 lks. dist. mkd. T22S R9W S20 BT.

Reset wooden stake alongside iron post.

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17927)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

(Corner Report)

The sec. cor. monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with 1975 brass cap, from which the remains of the original bearing trees:

A Fir 30" dia., bears N.8°E., 49 lks. dist. with healed blaze.

A Fir stump 28" dia., bears S.8°E., 64 lks. dist. with old axe marks visible on decayed blaze. (Rec. 72 lks.)

A root hole, bears S.71°W., 73 lks. dist. with a downed Fir 44" dia., alongside, with illegible scribe marks visible on decayed blaze.

and the bearing trees mkd. by Wofford, etal,

A Fir 11" dia., bears S.15¼°E., 19½ lks. dist. with healed blaze. (Rec. S.1½°E., 29 lks.)

A Hemlock 10" dia., bears S.57°W., 42½ lks. dist. with healed blaze. (Rec. S.37°W., 36 lks.)

A Fir 23" dia., bears N.10 3/4°W., 152 lks. dist. with healed blaze. (Rec. N.13½°W., 144 lks.)