

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec cor for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1619)

Set post corner to secs. 8, 9, 16 and 17, from which
A Fir 40" dia., bears S.43°E., 437 lks. dist.
Raised mound, with trench, as per instructions.

GL0 survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1666-67)

As all evidence of the corner to secs. 8, 9, 16 and 17, had been destroyed, I re-establish it, as follows:
Set Fir post, 4½ ft. long, 4" sq., 24" in the ground, for corn. to secs. 8, 9, 16 and 17, marked T22S S9 on the NE.; R9W S16 on the SE.; S17 on the SW.; and S8 on the NW. faces, with 4 notches on the S. and E. edges, from which,
An Oak 7" dia., bears N.40°E., 58 lks. dist. mkd. T22S R9W S9 BT.
An Oak 7" dia., bears S.66°E., 125 lks. dist. mkd. T22S R9W S16 BT.
An Oak 6" dia., bears S.73°W., 203 lks. dist. mkd. T22S R9W S17 BT.
An Oak 7" dia., bears N.35°W., 213 lks. dist. mkd. T22S R9W S8 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon "Ray" Tracy, crew - June, 1962 - C.S. File 49/103-7

Found - Oak tree, S.73°W., 134.0 ft. Tree dead and broken off just above BT scar. Top portion badly burned. Found good reverse scribing "BT" just below where tree was broken.
No trace of any other BTs found.
1½" Iron pipe, 9" above ground, N.73°E., 2.5 ft. from corner.

Set Brass cap at cor. mkd: County Surveyors Office

T 22 S R 9 W
S 8 S 9
S 17 S 16
1962

New BTs -13" Fir S.56°W., 134.1 ft. mkd. T22S R9W S17 CS BT.
17" Fir N.67°E., 24.7 ft. mkd. T22S R9W S9 CS BT.
11" Fir N.35°W., 106.0 ft. mkd. T22S R9W S8 CS BT.
15" Fir N.86°W., 35.0 ft. mkd. T22S R9W S8 CS BT.
No trees available to SE.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec cor for 8, 9, 16 and 17

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

BLM resurvey by James E. Jelley, under Group # 709, surveyed May/Sept. 1970 (DCSO records Vol. 36 Page(s) 14903-04)

The Sec. cor., perpetuated and recorded by the County in 1962, monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground, with a 1962 brass cap, from which the remaining original bearing tree

An Oak stump 10" dia., bears S.71½°W., 203 lks. dist. with fragmentary scribe marks in negative, visible on the overgrowth. (Rec. S.73°W.)

and a reference monument of no record:

An Iron pipe 2" dia., firmly set, projecting 10" above ground, bears N.64½°E., 3½ lks. dist.

and bearing trees mkd. by the County in 1962:

A Fir 20" dia., bears N.65°E., 32 lks. dist. with healed blaze.

A Fir 15" dia., bears S.56°W., 203 lks. dist. with healed blaze.

A Fir 20" dia., bears N.86½°W., 53 lks. dist. with healed blaze.

A Fir 15" dia., bears N.37°W., 161 lks. dist. with healed blaze.

and new bearing trees:

A W.Fir 8" dia., bears S.51°E., 19½ lks. dist. mkd. T22S R9W S16 BT.

A Fir 5" dia., bears S.5 3/4°W., 25 lks. dist. mkd. T22S R9W S17 BT.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1367, surveyed Apr./June 1987 - (DCSO records Vol. 45 Page(s) 18431)

The sec. cor., perpetuated and recorded by Godfrey and Tracy in 1962, from original evidence no longer in existence, monumented with an iron post, 1¾" dia., firmly set, projecting 8" above ground, with 1962 County brass cap, from which bearing trees mkd. by Godfrey and Tracy:

A Fir 26" dia., bears N.67°E., 37½ lks. dist. with healed blaze.

A Fir 28" dia., bears S.55°W., 203 lks. dist. with healed blaze.

A Fir 26" dia., bears N.86°W., 53 lks. dist. with healed blaze.

A Fir 20" dia., bears N.35½°W., 160½ lks. dist. with healed blaze.

and a new bearing tree:

(Cont. Next Page)

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 18" dia., bears S.50¼°E., 19½ lks. dist. mkd. T22S R9W S16 BT.

From this point, a point established by person(s) unknown, recorded by Godfrey in 1962, bears N.73°00'E., 0.038 chs. dist. monumented with an iron pipe 2" dia. firmly set, projecting 8" above ground.

Fd. B.C., Feb. 1985 by R. Hintz - M 98-37

Fd. & used on Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCS0 records Vol. 52 Page(s) 19865)

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/13/2001 - C.S. File 66/21-31

Found - 1962 DCS0 brass cap/iron pipe protrudes 10" above ground.
1½" I.D. iron pipe protrudes 8" out of ground bears N.73°E., 2.5'.
17" now 28" dia., 4 ft. high D.Fir stump with a fully healed single blaze, bears N.67°E., 24.7 ft. (1962)
5" now 18" dia., 3 ft. high D.Fir stump with a fully healed blaze, bears S.5¾°W., 16.5 ft. (1970)
18" now 24" dia., 4 ft. high D.Fir stump with fully healed single blaze S.50¼°E., 12.9 ft. (1987)
No other BTs found.
New - 11" dia., Pistol butt Maple double blazed & scribed "T22S R9W S16 CS BT" bears S.8½°E., 43.0 ft. to center of root crown.
7" dia., D.Fir double blazed & scribed "T22S R9W S17 CS BT" bears S.84½°W., 218.8 ft.
22" dia., W.Oak double blazed & scribed "T22S R9W S9 CS BT" bears N.31½°E., 194.9 ft.
5/8" iron rod protrudes 3" out of ground, bears S.80°W., 203.2 ft.
Compass decl. 17¾°E.

Fd. Ok by K DeGroot, 4/2005 - 2005-0042