

PRIMARY CORNER DESCRIPTION AP on line between Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon & Charles Gardner, Deputy Surveyors under Contract #52, dated Feb. 17, 1855 - (DCSO records Vol. 4 Page(s) 1620)

Set post, from which
A Fir, 12" dia., bears S.8°E., 35 lks.
A Fir, 20" dia., bears S.23°W., 35 lks.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1666-67)

Set Fir post, 4½ ft. long, 4" sq., 24" in the ground, marked F.S.9 on the E, and F.S.8 on the W faces, from which
A Fir, 20" dia., bears S.8°E., 35 lks. marks over grown.
A Fir, stump, 36" dia., bears S.34½°W., 35 lks.
The SE corner of the DL Claim of Edward Spicer, bears N.54°W., 134 lks.

Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19866)

The angle point between secs. 8 & 9, determined at record bearing and distance from the remains of the bearing tree mkd. by Worrick:

A decayed fir stump, size indeterminate, bears S.8°E., 35 lks., with scribe marks S9 T22S R9W visible on an opened face.

At the corner point
Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

AP
T 22 S R 9 W
S 8 S 9
1998

from which
A fir, 24" diam., bears N.18½°E., 18 lks., mkd. AP S9 BT.
A fir, 16" diam., bears N.32°W., 37½ lks., mkd. AP S8 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.