

PRIMARY CORNER DESCRIPTION Sec cor for 4 & 9 on E bdy of S 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1671)

Intersected N. and S. line, 3.90 chs. S. of the corner to secs. 5 and 8.
 Set Fir post 4½ ft. long, 4" sq., 24" in the ground on hillside sloping SW. for closing corner to secs. 5 and 8*, marked T22S S5 on the N.; C.C. on the E.; R9W S8 on the S. sides, with 5 grooves on the S. and E. sides, from which,
 An Oak 6" dia., bears N.67°E., 69 lks. dist. mkd. T22S R9W S5 BT.
 A Fir 18" dia., bears S.52°E., 23 lks. dist. mkd. T22S R9W S8 BT.
 A Fir 10" dia., bears S.82°W., 25 lks. dist. mkd. C.C. T22S R9W S5-8 BT.

*(Subsequent renewals call this corner, the corner for 4 and 9 only.) V. Laugen, June 1995

V. T. Hosford - For:Evans Products Co. - Aug. 1954 - C.S. File 41/292 and M 10-80

I find the closing corner to secs. 4 & 9, at which point I set a 3" Fir post marked C.C. S4 & 9. The 2 original Fir BTs are dead, but standing. No evidence could be found of the Oak.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - Oct. 18, 1971 - C.S. File 53/66-128

Found - 10" D.Fir now 30 ft. snag, S.82°W., 16.5 ft., scribe visible.
 18" D.Fir now 20 ft. snag, S.52°E., 15.2 ft., shows scar.

Set Brass cap at C.C. mkd: County Surveyors Office
 T 22 S R 9 W
 S 8 | S 4 C.C.
 S 9
 1971

(Excavation for brass cap was made to hard sandstone.)
 New BTs -16" D.Fir S.56½°E., 40.7 ft. scribed T22S R9W S9 CC CS BT.
 6" D.Fir N.74°E., 12.6 ft. scribed CC S4 CS BT.
 This cor. lies on steep SW slope. Cap set shallow in mound of stones about 2 chs. West of ridge top.

Continued next page

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. cor. for 4 & 9 on E. bdy of S. 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. & used on Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19867-8)