

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 4 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by V.T. Hosford, - For: Evans Products Co. - Aug. 1954
C.S. File 41/292 and M 10-80

At proportionate distance, I establish the West ¼ S 4. At this corner, I set a 4" Fir limb post marked ¼ S 4, P.S. 253, from which,
A Fir 24" dia., bears N.46°E., 56.9 ft. mkd. ¼ S4 PS 253 BT.
A root of a 60" Fir bears S.35°E., 4.1 ft. marked ¼ S4 PS 253 BT.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1281, surveyed Aug/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18192-93)

The ¼ sec. cor. of sec. 4 only, established by proportionate measurement and recorded by Hosford in 1954, when the original ¼ sec. cor. of sec. 5 only was still in existence, and is accepted as the corner, monumented with a decayed wood post, 2" dia., loosely set, projecting 2 ft. above ground, from which bearing trees mkd. by Hosford:

- A Fir 31" dia., bears N.47¼°E., 87 lks. dist. with healed blaze.
- A root, 10" dia., of a Fir, 60" dia., bears S.35°E., 6 lks. dist. with healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 15" in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:

T 22 S R 9 W
¼ S 4
1985

from which a new bearing tree and bearing object:
An Alder 5" dia., bears S.79°E., 53 lks. dist. mkd. ¼ S4 BT.
The marks X BO on rock face, bears South, 1 lks. dist.
The corner is located on shelf of steep rock face, 35 ft. high, sloping NW.

Fd & used on Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19877)