

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 340240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM subdivision of section by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17948)

Point for the center ¼ sec. cor. of sec. 28, at intersection with the E. and W. center line.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S R 9 W
C ¼ S 28

1984

from which

A Fir 33" dia., bears N.47¼°E., 49 lks. dist. mkd. C ¼ S28 BT.

A Fir 18" dia., bears S.85½°W., 12½ lks. dist. mkd. X BT.

Tony Hostetter - For: Roseburg Resources - 11/2023 - M183-16

Found - 1984 brass cap as set by BLM, from which
37" Fir, face evident, BLM tag, N.47¼°E., 32.3 ft. to center.

24" Fir, no marks, S.85½°W., 8.3 ft. to center.
New BTs- 38" Fir, marked "X", BT tag, bears S.17°02'E., 1.9 ft to spike, below "X"
10" Fir, marked "X", BT tag, bears S.30°03'E., 26.3 ft to spike, below "X"

Note - BT tags placed on New BTs list measurements from a 6" spike, placed in the root collar below the "X" to the corner monument.