

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1695-96)

-----  
Set Fir post 5 ft. long, 4" sq., 30" in the ground, for 1/4 sec. corner, marked 1/4 S on the N. face, from which,  
A Fir 24" dia., N.22°30'W., 55 lks. dist. mkd. 1/4 S BT.  
A Fir 30" dia., bears S.15°E., 31 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16055)

-----  
The 1/4 sec. cor. of secs. 21 and 28, determined at record distance from the original bearing trees:  
A Fir 55" dia., bears N.15°E., 55 lks. dist. with illegible scribe marks visible on open blaze. (Rec. N.22 1/2°W.)  
A Fir 41" dia., bears S.22 1/2°E., 31 lks. dist. with healed blaze. (Rec. S.15°E.)

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:  
T 22 S R 9 W  
1/4 S 21  
S 28  
1975

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17926)

-----  
The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2" dia., firmly set, projecting 8" above ground, with brass cap mkd:  
T 22 S R 9 W  
1/4 S 21  
S 28  
1975

from which the remains of the original bearing trees:  
A Fir 57" dia., bears N.11°E., 55 lks. dist. with illegible scribe marks visible on open blaze. (Rec. N.15°E.)  
A Fir snag, 42" dia., bears S.22 1/2°E., 31 lks. dist. with healed blaze.  
and a new bearing tree:  
A Fir 13" dia., S.48 1/4°W., 37 lks. dist. mkd. 1/4 S28 BT.

CONT.

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Les Roberts, PLS #1039 - For: International Paper Co. - Oct. 12, 1983 (added to record 11/30/2023) - M 96-24 and C.S. File 58/280

-----  
Found - 42" Fir S.25°E., 20.2' (scar vis.) 1894 BT  
58" Fir N.11°E., 35.0' (scar vis.) 1894 BT

Tony Hostetter - For: Roseburg Resources - 11/2023 - M183-16

-----  
Found - 1975 BLM brass cap as described by Roberts (M96-24)  
48" Fir, face evident, N.11°E., 35.0 ft to center.  
42" Fir stump, no marks, bears S.25°E., 20.2 ft. to center.

New BTs- 12" Fir, marked "X", BT tag, bears S.75°45'E., 7.1 ft to spike, below "X"  
11" Fir, marked "X", BT tag, bears S.53°10'E., 7.9 ft. to spike, below "X"  
14" Fir, marked "X", BT tag, bears N.77°56'E., 8.0 ft. to spike, below "X"

Note - BT tags placed on New BTs list measurements from a 6" spike, placed in the root collar below the "X" to the corner monument.