

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1668-69)

Set Fir post, 5 ft. long, 4" sq., 24" in the ground, on hillside, sloping NW. for 1/4 sec. corner, mkd. 1/4 sec. on the N. face, from which
A Fir 30" dia., bears N.20°30'E., 55 lks. dist. mkd. 1/4 S BT.
A Fir 60" dia., bears S.20°30'W., 10 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1367, surveyed Apr/June 1987 - (DCSO records Vol. 45 Page(s) 18432)

The 1/4 sec. cor., determined at record bearing and distance from the remains of the original bearing trees:
A sawed Fir stump 40" dia., bears N.20 1/2°E., 55 lks. dist. with scribe marks BT visible on opened blaze.
A sawed Fir stump 60" dia., bears S.20 1/2°W., 10 lks. dist. with scribe marks S BT visible on opened blaze.
At the corner point
Set a stainless post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:
T 22 S R 9 W
1/4 S 9
 S 16
 1987
from which new bearing trees:
A Fir 9" dia., bears N.26 1/4°E., 22 lks. dist. mkd. 1/4 S9 bT.
A Fir 11" dia., bears S.49 3/4°E., 28 1/2 lks. dist. mkd. 1/4 S16 BT.
Deposit a white "DEEP-1" magnetic marker at the base of stainless steel post.