

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by V. W. Hosford - Aug. 10, 1954 - C.S. File 41/292 and M 10-80

-----  
At this corner, I set a 1½" Iron pipe and a 4" Hemlock post, mkd. ¼ S4, from which

A dead Fir 24" dia., bears N.72°E., 55.6 ft. mkd. ¼ S4 PS253 BT.

A Fir stump 48" dia., bears S.29½°W., 26.8 ft. mkd. ¼ S4 PS253 BT.

Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19874)

-----  
The center ¼ cor. of sec. 4, established by Hosford, in 1954, recorded in the Douglas County Courthouse file Nos. 41-292 and M 10-80, & is accepted as the corner; monumented with an iron pipe, 1½" diam., firmly set, projecting 18" above ground, from which the remains of a bearing tree mkd. by Hosford:

A fir stump, 48" diam., bears S.29½°W., 42½ lks., with scribe marks 4 S PS253 BT visible on an open face.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T 22 S R 9 W

C 1/4 S 4

1996

A fir, 14" diam., bears S.51°E., 13 lks., mkd. C¼ S4 BT.

A fir, 10" diam., bears S.20°W., 44½ lks., mkd. X BT.

Deposit iron pipe and a magnet in a white plastic case at the base of the stainless steel post.