

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V. W. Hosford - For: Evans Products Co. - Aug. 1954 - C.S. File 41/292 and M 10-80

-----  
At proportionate distance, I establish the North  $\frac{1}{4}$  S 4. At this corner, I set a 4" Fir post marked " $\frac{1}{4}$  S4 PS 253", from which

A Fir 40" dia. bears S.57°E., 87.0 ft. marked  $\frac{1}{4}$  S4 PS 253 BT.

Douglas County Surveyors Office - John M. Powell, Deputy - C.S. File 53/66-135 - Sept. 1971

-----  
Corner searched for, not found.

Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19858-9)

-----  
Point for the  $\frac{1}{4}$  sec. cor. of sec. 4 only, T. 22 S., R. 9 W. Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T21S  
 $\frac{1}{4}$  S 4  
T22S R9W  
1996

from which

A fir, 9" diam., bears S.80 $\frac{1}{4}$ °E., 10 $\frac{1}{2}$  lks., mkd.  $\frac{1}{4}$  S4 BT.

A fir, 6" diam., bears S.65 $\frac{1}{2}$ °W., 18 $\frac{1}{2}$  lks., mkd. X BT.

Deposit a magnet in a white plastic case at base of stainless steel post.