

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 279 survey dated March 5, 1878 (DCSO records Vol. 4 Page(s) 1650)

 Set Fir post 5" dia., 4 ft. long, for the corner to secs. 3, 4, 33 and 34, from which
 A Fir 24" dia., bears N.50°E., 36 lks. dist.
 A Fir 24" dia., bears S.40°E., 27 lks. dist.
 A Fir 30" dia., bears S.30°W., 90 lks. dist.
 A Fir 24" dia., bears N.45°W., 68 lks. dist.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Dec. 1967 - C.S. File 54/60-14

 Found - Orig. 24" now 42" Fir, alive, N.50°E., 23.8 ft. (slope), bark scribing visible in poor condition.
 Orig. 30" now 40" Fir, alive, S.30°W., 59.4 ft., bark scribing visible.

Set Brass cap at cor. mkd: County Surveyors Office
 T22S R9W S 33 | S 34
 T23S S 4 | S 3
 1967

New BTs -12" Hemlock N.2°W., 32.2 ft. mkd. T22S R9W S33 CSBT
 8" Maple N.8°E., 18.5 ft. mkd. T22S R9W S34 CS BT.
 8" Hemlock S.16°W., 82.7 ft. mkd. T23S R9W S4 CS BT.
 8" Hemlock S.28°E., 74.2 ft. mkd. T23S R9W S3 CS BT.

This corner lies on very steep, westerly slope approx. 175 ft. West of ridge top.

Survey by W. Carey Weatherly - For: International Paper Co. -Aug. 1982 - C.S. File 58/27691

 Found - Iron fence post which had been placed, by me, along side corner monument in 1980 and five BTs listed below.

Drove a Douglas County Surveyor's 30" x 1" galv. I.P. with 1967 brass cap which had been removed by I.P. Co. cutting crew, alongside the fence post, from which

 34" D.Fir stump with IPCo tag bears N.35°E., 23.5 ft
 6" burnt Hemlock stob with IP Co. tag, bears S.29½°E., 77.0 ft.
 14" Hemlock stump with IP Co. tag S.14¼°W., 78.7 ft.
 42" D.Fir stump with IPCo tag bears S.27°W., 57.3 ft
 15" Hemlock stump, scribing visible, with IP Co. tag, bears N.01°W., 34.4 ft.

BTs in Secs. 3 & 4 treated with pentachlorophenol and covered with galv. metal.

Cont.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23211-2)

The cor. of secs. 3, 4, 33, & 34, perpetuated by the Douglas Co Surveyor's Office in, 1967, further perpetuated by Weatherly, in 1982; monumented with an iron post, 1 1/4" dia., firmly set, projecting 6" above the top of a mound of stone, 3 ft. base, 1 1/2 ft. high, with a brass cap (properly) mkd. from which the remains of the original bearing trees

A decayed fir stump, 33" dia., bears N.35 1/4°E., 23.7 ft., no marks visible. (Record, N.50°E.)

A fir stump with an aluminum cap, 46" dia., bears S.27 1/4°W., 57.0 ft., no marks visible. (Record, S.30°W., 59.4 ft.)

and the remains of the BTs mkd. by the Douglas Co Surveyor's Office

A burnt hemlock stump with an aluminum cap, size indeterminate, bears S.30 1/4°E., 77.2 ft., no marks visible.

A burnt hemlock stump with an aluminum cap, 17" dia., bears S.13 3/4°W., 78.2 ft., no marks visible.

A decayed hemlock stump, size indeterminate, bears N.1°W., 34.3 ft., with scribe marks 22S R9W S33 CS BT visible on open blaze.

and new bearing trees

A fir, 11" dia., bears N.27°E., 22.2 ft., mkd. T22S R9W S34 BT.

A fir, 11" dia., bears S.42 1/2°E., 50.1 ft., mkd. T23S R9W S3 BT.

A fir, 12" dia., bears S.36 1/4°W., 11.0 ft., mkd. T23S R9W S4 BT.

A fir, 13" dia., bears N.35°W., 28.5 ft., mkd. T22S R9W S33 BT.

Each new bearing tree has a 2 1/2"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.

NAD 1983 (2011)

Latitude: 43°36'32.15" N. Longitude: 123°46'00.12"W.