

PRIMARY CORNER DESCRIPTION Sec. cor. for 15, 16, 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1636)

-----

Set a Maple post 40" long, 5" dia., for the corner to secs. 15, 16, 21 and 22, from which

- A Fir 30" dia., bears N.30°E., 169 lks. dist.
- A Fir 12" dia., bears S.10°E., 83 lks. dist.
- A Fir 24" dia., bears S.18°W., 233 lks. dist.
- A Fir 60" dia., bears N.10°W., 25 lks. dist.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1708)

-----

At the Sec. cor., which I re-established, as follows:

Set Maple post, 4½ ft. long, 4" sq., 24" in ground on hillside sloping West, mkd. T22S S15 on the NE.; R9W S22 on the SE.; S21 on the SW.; and S16 on the NW. faces with 3 notches on the S. and E. edges, from which:

- A Fir 30" dia., bears N.30°E., 155 lks. dist. mkd. T22S R9W S15 BT.
- A Fir 24" dia., bears S.18°W., 239 lks. dist. mkd. T22S R9W S21 BT.
- A Fir 60" dia., bears N.10°W., 25 lks. dist. mkd. T22S R9W S16 BT.

I marked:

- A Maple 8" dia., bears S.11°E., 80 lks. dist. mkd. T22S R9W S22 BT.

Practically agreeing with field notes furnished me by the U.S. Surveyor General.

Survey by H.T. Lewis, Engineer #722 - Sept. 28, 1939 - C.S. File 16/55 (and "old" corner book, page 28) (recorded by H.L. Eppstein)

-----

At the corner of secs. 15-16-21-22, I found the SW witness tree in good shape and evidences of the NW and NE trees, but no evidence of the corner post. I therefore

Set a Fir post 4 ft. long, 4" dia., 18" in ground, from which

- A Fir 10" dia., bears S.84°E., 11 ft. dist. mkd. T22S R9W Sec. 22 BT 722.
- A Fir 16" dia., bears N.45°E., 9 ft. dist. mkd. T22S R9W sec. 15 BT 722.
- A Fir 13" dia., bears N.40°W., 54 ft. dist. mkd. T22S R9W Sec. 16 BT 722.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 15, 16, 21 and 22

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V Perron, crew - Feb. 29, 1968 - C.S. File 54/60-43

-----

Found - BTs as recorded by Lewis, 1939.

10" now 15" Fir, alive, S.84°E., 11.0 ft., shows very good scar.

16" now 16" Fir, alive, N.45°E., 9.0 ft., shows good scar.

13" now 27" Fir, alive, N.40°W., 54.0 ft. opened and shows "722" scribe. Rescribed: T22S R9W S16 CS BT.

No remains of NW original BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 22	S R	9 W
S 16		S 15
S 21		S 22
1968		

New BT - 25" D.Fir S.66°W., 33.6 ft. mkd. T22S R9W S21 CSBT  
This corner lies on NW side of ridge.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16050)

-----

The Sec. cor., perpetuated and recorded by Lewis in 1939, and further perpetuated by Godfrey in 1962, (rec. 1968) monumented with an iron post 2" dia., firmly set, projecting 8" above ground with a county brass cap, from which the remains of the original bearing trees:

A decayed Fir stump 68" dia., bears N.10°W., 25 lks., no marks visible.

and bearing trees mkd. by Lewis:

A Fir 16" dia., bears N.45°E., 15 lks. dist., with healed blaze.

A Fir 16" dia., bears S.84°E., 17 lks. dist., with healed blaze.

A Fir 35" dia., bears N.40°W., 82 lks. dist., with healed blaze.

and a bearing tree mkd. by Godfrey

A Fir 29" dia., bears S.66°W., 51 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron post, with brass cap mkd:

T 22	S R	9 W
S 16		S 15
S 21		S 22
1973		

(Cont. Next Page)

