

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. cor. for 4 & 9 only (E bdy. S.10)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1663)

-----  
Set sandstone 12x8x8, 9" in ground on hillside sloping W. for corner to 3, 4, 9 and 10, marked with 5 notches on the S., and 8 notches on the E. sides, from which,

- A Fir 24" dia., bears N.53°30'E., 80 lks. dist. mkd. T22S R9W S3 BT.
- A Maple 12" dia., bears S.61°E., 47 lks. dist. mkd. T22S R9W S10 BT.
- A Hemlock 18" dia., bears S.26°30'W., 84 lks. dist. mkd. T22S R9W S9 BT.
- A Hemlock 8" dia., bears N.27°30'W., 15 lks. dist. mkd. T22S R9W S4 BT.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1367, surveyed Apr/June 1987 - (DCSO records Vol. 45 Page(s) 18427-28)

-----  
Point for the cor. of secs. 4 and 9 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S R 9 W  
    S 4 S 10  
    S 9  
    1987

from which

- A Fir 14" dia., bears S.5½°W., 30½ lks. dist. mkd. T22S R9W S9 BT.
- A Fir 11" dia., bears N.51°W., 24 lks. dist. mkd. T22S R9W S4 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Found OK by T. Rambo, Oct. 2000 - M136-12