

PRIMARY CORNER DESCRIPTION Sec. cor. for 3 & 10 only (E. bdy S. 4)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1664-65)

Intersected N. and S. line 218 lks., N.0°05'E., the cor. to secs. 4 and 9. Set sandstone 14x12x6, 10" in grond on steep hillside, sloping SW. for closing corner to sec. 3 and 10 mkd. C.C. on the E. with 8 notches on the E. and 5 notches on the S. side, from which

A Fir 36" dia., bears N.40°E., 82 lks. dist. mkd. T22S R9W S3 BT.

A Fir 56" dia., bears S.67°E., 43 lks. dist. mkd. T22S R9W S10 BT.

A Fir 60" dia., bears N.68°W., 11 lks. dist. mkd. C.C. T22S R9W S3 and 10 BT.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1367, surveyed Apr/June 1987 - (DCSO records Vol. 45 Page(s) 18428)

Point for the closing cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S R 9 W
S 4 $\frac{S 3}{S 10}$ CC
1987

from which

A Fir 11" dia., bears N.6 3/4°E., 35 lks. dist. mkd. T22S R9W S3 CC BT.

A Fir 18" dia., bears S.65¼°E., 61 lks. dist. mkd. T22S R9W S10 CC BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.