

PRIMARY CORNER DESCRIPTION SE cor. Sec. 28 (SW cor. Sec. 27)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1693)

-----  
I set Maple post, 4½ ft. long, 4" sq., 24" in the ground at the point of intersection for the closing corner to secs. 27 and 28, marked T22S S27 on the East, R9W S28 on the West, and C.C. on the North faces with 1 groove on the S. and 3 grooves on the E. sides, from which,  
A Fir 24" dia., bears N.9°E., 100 lks. dist. mkd. T22S R9W S27 BT.  
A Fir 40" dia., bears S.30°E., 26 lks. dist. mkd. C.C. T22S R9W S27-28 BT.  
A Fir 20" dia., bears N.49°W., 104 lks. dist. mkd. T22S R9W S28 BT.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16047-48)

-----  
(33.46 chs.)  
The original closing cor. of secs. 27 and 28, determined from the remains of the original bearing trees:  
A Fir 20" dia., bears N.9°E., 104 lks. dist., no marks visible on decayed blaze. (Rec. 100 lks.)  
A Fir 48" dia., bears S.30°E., 26 lks. dist., with illegible scribe marks visible on open blaze.  
A Fir 38" dia., bears N.49°W., 100 lks. dist., with illegible scribe marks visible on open blaze. (Rec. 104 lks.)

(34.40 chs. S.1°16'E.)  
Intersect the N. bdy. of sec. 34, and true point for the closing cor. of secs. 27 and 28.  
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd:  
T 22 S R 9 W  
C C  
S 28 S 27  
S 34  
1974

from which  
A Fir 21" dia., bears N.38½°E., 48 lks. dist. mkd. T22S R9W S27 CC BT.  
A Fir 44" dia., bears N.61p°W., 65 lks. dist. mkd. T22S R9W S28 CC BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION SE cor. Sec. 28 (SW cor. Sec. 27)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Corrective Dependent resurvey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17918-19)

(33.79 chs.)

The original closing cor. of secs. 27 and 28, perpetuated by person(s) unknown, monumented with an iron pipe, 1 3/4" dia., firmly sset, projecting 12" above ground, from which the remains of the original bearing trees:

- A Fir snag, size indeterminate, bears N.9°E., 104 lks. dist., with no marks remaining.
- A sawed Fir stump 48" dia., bears S.30°E., 26 lks. dist., with illegible scribe marks visible on opened blaze.
- A sawed Fir stump 38" dia., bears N.49°W., 100 lks. dist., with illegible scribe marks visible on open blaze.

(34.70 chs., S.0°22'E.)

Intersect the N. bdy. of sec. 34.

True point for the closing cor. of secs. 27 and 28.

From this point the closing cor. of secs. 27 and 28, erroneously established by Wofford, etal, 1973-79, bears S.26°40'E., 0.04 chs. dist., monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point, Reset the iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

```

T 22 S    R 9 W
  S 28    S 27
-----
    C C
    S 34
    1984

```

from which bearing trees mkd. by Wofford, etal,

- A Hemlock 21" dia., bears N.43 1/4°E., 47 lks. dist., with scribe marks S27 CC BT visible on partially healed blaze.
- A Fir 45" dia., bears N.66 1/2°W., 59 lks. dist., with healed blaze.