

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1636)

Set boulder stone 18 x 8 x 8 ins., 9" in ground. Made mound of three other large stones, for ¼ sec. corner. No trees near.

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16051)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 9 W
¼ $\frac{S\ 15}{S\ 22}$
1975

from which

- A Fir 19" dia., bears N.17°E., 8 lks. dist. mkd. ¼ S15 BT
- A Fir 22" dia., bears S.16°E., 27 lks. dist. mkd. ¼ S22 BT