

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 4 Page(s) 1628)

Set a maple post, 5 ft. long, 6" dia., 20" in ground, for ¼ sec. cor., from which

- A Fir, 8" dia., bears S.65°E., 17 lks.
- A Fir, 5" dia., bears N.62°W., 18 lks.

Fd. & used on GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1714)

Troy Rambo, Mulkins & Rambo LLC - For: Roseburg Resources Co.
- Oct. 2000 - M 136-12

Set - 5/8"x30" rebar w/2" alum. cap.
Bark scribed "¼ S15 BT" on a 16" Maple, bears S.68°E., 5.4 ft.

- 6' line post on ridge top bears N.89°W., 42.0 ft.
- 6' steel post bears N.46°W., 11.3 ft.
- 6' steel post bears South 4.3 ft.

Note- All steel posts have BT tags attached.