

TOWNSHIP 22 RANGE 09 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1664)

Set sandstone 16x12x6, 12" in ground on steep hillside sloping SE for 1/4 sec. cor, marked 1/4 on N face, from which
A Maple, 16" dia., bears N.34°E., 34 lks., mkd: 1/4 S BT.
A Maple, 18" dia., bears S.51°W., 41 lks., mkd: 1/4 S BT.

Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19863)

The 1/4 sec. cor. of secs. 3 & 10, perpetuated from original evidence no longer in existence by International Paper Co., now Roseburg Lumber Co., recorded in their office at Reedsport, Oregon; monumented with an iron pipe, 1" diam., firmly set, projecting 6" above the ground.

At the corner point
Set a stainless steel post, 28" long, 2 1/2" diam., 24" in the ground, with brass cap mkd.

T 22 S R 9 W
 S 3
1/4 S 10
 1996

from which new bearing trees
A fir, 20" diam., bears S.3 3/4°W., 38 1/2 lks., mkd. 1/4 S10 BT.
A fir, 14" diam., bears N.75 1/2°W., 21 lks., mkd. 1/4 S3 BT.
Deposit iron pipe and a magnet in a white plastic case at the base of the stainless steel post.