

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 279 survey dated March 5, 1878 (DCSO records Vol. 4 Pg 1650)

-----  
Set a Fir post 5" dia., 4 ft. long, 18" in ground, for the corner to secs. 2, 3, 34 and 35, from which  
A Fir 60" dia., bears N.60°E., 71 lks. dist.  
A Fir 14" dia., bears S.20°E., 99 lks. dist.  
A Fir 30" dia., bears S.50°W., 15 lks. dist.  
A Fir 24" dia., bears N.20°W., 25 lks. dist.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Dec. 1967 - C.S. File 54/60-11

-----  
Found - 1½" I.P. and iron cap at corner. Unrecorded  
Orig. 60" now 66" Fir, alive, N.60°E., 46.9 ft., fragmentary bark scribe.  
Orig. 30" now 32" Fir, decayed stump, S.50°W., 29.7 ft. (not 9.9 ft.), no scribe.  
Orig. 14" now 28" Fir stump, S.20°E., 65.3 ft., opened and find "B".

Set Brass cap at cor. mkd: County Surveyors Office  
T22S R9W S 34 | S 35  
T23S R9W S 3 | S 2  
1967

Deposit old corner pipe alongside.  
New BTs -7" D.Fir N.49°E., 30.0 ft. mkd. T22S R9W S35 CS BT.  
14" D.Fir N.55°W., 50.1 ft. mkd. T22S R9W S34 CS BT  
15" Hemlock S.79°W., 43.6 ft. mkd. T23S R9W S3 CSBT  
17" D.Fir S.40°E., 39.9 ft. mkd. T23S R9W S2 CS BT.  
This corner lies on NW slope of spur, sloping West.

Fd. and used in BLM survey by Wofford and Malloy, under Group #1074, surveyed July 1980/Nov. 1982 - (DCSO records, Vol. 43 Page 16855)

Fd. Brass cap, June 1984, by R. Hintz, M 97-6

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23213-4)

-----  
The cor. of secs. 2, 3, 34, & 35, perpetuated by the Douglas Co Surveyor's Office in December, 1967; monumented with an iron post, 1½" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A fir stump, 74" dia., bears N.60°E., 46.9 ft., no marks visible.  
continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A decayed fir stump, 28" dia., bears S.50°W., 29.7 ft., no marks visible.  
and the remains of the BTs mkd. by the Douglas Co Surveyor's Office

A fir, 25" dia., bears N.49°E., 30.4 ft., with a healed blaze.

A fir stump, 6 ft. high, 31" dia., bears S.40°E., 39.6 ft., with a healed blaze.

A decayed hemlock stump, 25" dia., bears S.79°W., 43.6 ft., no marks visible.

and new bearing trees

A fir, 16" dia., bears S.22°E., 51.8 ft., mkd. T23S R9W S2 BT.

A fir, 11" dia., bears S.17½°W., 33.6 ft., mkd. T23S R9W S3 BT.

A fir, 14" dia., bears N.37¾°W., 32.3 ft., mkd. T22S R9W S34 BT.

Alongside the cor. is an iron post, 36" long, 1½" dia., disturbed, with an unmarked iron cap. Bury iron post alongside the cor.

Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.